there are at least four of the fluid compartments along side wall sections; and

when one of the compartments ruptures during tampering, another of the compartments is configured to retain fluid therein.

25. A medication bottle comprising:

(a) a medication-container;

(b) a cap removeably coupled to the container;

(c) a first sensor mounted on one of the container or cap;

(d) at least a second sensor mounted on one of the container or cap;

(e) an electrical circuit located on at least one of the container or cap;

(f) an actuator operably actuated by the circuit depending on user authentication by signals from the sensors;

(g) a lock operably locked and unlocked by the actuator, the lock securing the cap to the container if the user has not been authenticated;

(h) at least one of the sensors being a biometric sensor; and

(i) an aversive fluid being releasable into the container.

26. The bottle of claim **25**, wherein the sensors and the circuit are mounted to the cap.

27. The bottle of claim **25**, wherein the biometric sensor scans a user's fingerprint.

28. The bottle of claim **25**, wherein at least one of the sensors includes a camera.

29. The bottle of claim **25**, wherein one of the sensors includes an RFID reader.

30. The bottle of claim **25**, wherein the fluid is located within separate compartments between multiple walls of the container, the walls being attached together between the fluid compartments.

31. Programmable software, stored in non-transient memory coupled to a bottle, the software comprising:

(a) first instructions reading user RFID data and comparing the user RFID data to stored RFID data;

(b) second instructions obtaining data associated with at least one of:

(i) a user fingerprint and comparing the user fingerprint data to stored fingerprint data; or

(ii) a camera-generated user image and comparing the user image data to stored image data; and

(c) third instructions unlocking a cap from a container of the bottle, which is portable, if the first and second instructions authenticate the user.

* * * * *